

SERIAL NO. CTL UNI # C24726

CYLINDRICAL TANK - THEORETICAL INAGE CALIBRATION

DIAMETER = 50.50 in. LENGTH = 492.00 in.
 G.P.I. = 8.67 in. HEAD GAL = 34.00 gal.

CAPACITY = 4334 gal.

| INCH | - 0 - | 1/4 | 1/2 | 3/4 | INCH | - 0 - | 1/4 | 1/2 | 3/4 |
|------|-------|------|------|------|------|-------|------|------|------|
| 0 | | 3 | 7 | 13 | 25 | 2140 | 2167 | 2194 | 2222 |
| 1 | 21 | 29 | 38 | 47 | 26 | 2249 | 2276 | 2304 | 2331 |
| 2 | 57 | 68 | 80 | 92 | 27 | 2358 | 2385 | 2413 | 2440 |
| 3 | 105 | 118 | 132 | 146 | 28 | 2467 | 2494 | 2521 | 2548 |
| 4 | 160 | 175 | 191 | 206 | 29 | 2575 | 2602 | 2629 | 2656 |
| 5 | 222 | 239 | 256 | 273 | 30 | 2683 | 2710 | 2736 | 2763 |
| 6 | 291 | 308 | 326 | 345 | 31 | 2790 | 2816 | 2843 | 2869 |
| 7 | 364 | 383 | 402 | 422 | 32 | 2896 | 2922 | 2948 | 2974 |
| 8 | 441 | 461 | 482 | 502 | 33 | 3000 | 3026 | 3052 | 3078 |
| 9 | 523 | 544 | 565 | 587 | 34 | 3104 | 3129 | 3155 | 3180 |
| 10 | 608 | 630 | 652 | 675 | 35 | 3205 | 3230 | 3255 | 3280 |
| 11 | 697 | 720 | 743 | 766 | 36 | 3305 | 3330 | 3354 | 3379 |
| 12 | 789 | 812 | 836 | 859 | 37 | 3403 | 3427 | 3451 | 3475 |
| 13 | 883 | 907 | 931 | 955 | 38 | 3498 | 3522 | 3545 | 3568 |
| 14 | 980 | 1004 | 1029 | 1054 | 39 | 3591 | 3614 | 3637 | 3659 |
| 15 | 1079 | 1104 | 1129 | 1154 | 40 | 3682 | 3704 | 3726 | 3747 |
| 16 | 1179 | 1205 | 1230 | 1256 | 41 | 3769 | 3790 | 3811 | 3832 |
| 17 | 1282 | 1308 | 1334 | 1360 | 42 | 3852 | 3873 | 3893 | 3912 |
| 18 | 1386 | 1412 | 1438 | 1465 | 43 | 3932 | 3951 | 3970 | 3989 |
| 19 | 1491 | 1518 | 1544 | 1571 | 44 | 4008 | 4026 | 4043 | 4061 |
| 20 | 1598 | 1624 | 1651 | 1678 | 45 | 4078 | 4095 | 4112 | 4128 |
| 21 | 1705 | 1732 | 1759 | 1786 | 46 | 4143 | 4159 | 4174 | 4188 |
| 22 | 1813 | 1840 | 1867 | 1894 | 47 | 4202 | 4216 | 4229 | 4242 |
| 23 | 1921 | 1949 | 1976 | 2003 | 48 | 4254 | 4266 | 4277 | 4287 |
| 24 | 2030 | 2058 | 2085 | 2112 | 49 | 4296 | 4305 | 4313 | 4321 |

* THEORETICAL CALIBRATION IS NOT INTENDED FOR LEGAL MEASUREMENT OF PRODUCT VOLUMES!