

SERIAL NO. UNIT C25309

CYLINDRICAL TANK - THEORETICAL INAGE CALIBRATION

DIAMETER = 49.25 in. LENGTH = 480.00 in.
 G.P.I. = 8.25 in. HEAD GAL = 30.00 gal.
 CAPACITY = 4018 gal.

| INCH | - 0 - | 1/4 | 1/2 | 3/4 | INCH | - 0 - | 1/4 | 1/2 | 3/4 |
|------|-------|------|------|------|------|-------|------|------|------|
| 0 | | 3 | 7 | 13 | 25 | 2048 | 2074 | 2100 | 2126 |
| 1 | 20 | 28 | 36 | 45 | 26 | 2152 | 2178 | 2204 | 2229 |
| 2 | 55 | 66 | 77 | 89 | 27 | 2255 | 2281 | 2307 | 2333 |
| 3 | 101 | 113 | 127 | 140 | 28 | 2358 | 2384 | 2410 | 2435 |
| 4 | 154 | 169 | 183 | 198 | 29 | 2461 | 2487 | 2512 | 2537 |
| 5 | 214 | 230 | 246 | 263 | 30 | 2563 | 2588 | 2613 | 2639 |
| 6 | 279 | 296 | 314 | 332 | 31 | 2664 | 2689 | 2714 | 2739 |
| 7 | 350 | 368 | 386 | 405 | 32 | 2763 | 2788 | 2813 | 2837 |
| 8 | 424 | 444 | 463 | 483 | 33 | 2862 | 2886 | 2910 | 2935 |
| 9 | 503 | 523 | 543 | 564 | 34 | 2959 | 2983 | 3007 | 3030 |
| 10 | 585 | 606 | 627 | 648 | 35 | 3054 | 3077 | 3101 | 3124 |
| 11 | 670 | 691 | 713 | 735 | 36 | 3147 | 3170 | 3193 | 3215 |
| 12 | 758 | 780 | 803 | 825 | 37 | 3238 | 3260 | 3283 | 3305 |
| 13 | 848 | 871 | 894 | 917 | 38 | 3327 | 3348 | 3370 | 3391 |
| 14 | 941 | 964 | 988 | 1011 | 39 | 3412 | 3433 | 3454 | 3475 |
| 15 | 1035 | 1059 | 1083 | 1108 | 40 | 3495 | 3515 | 3535 | 3555 |
| 16 | 1132 | 1156 | 1181 | 1205 | 41 | 3574 | 3594 | 3613 | 3632 |
| 17 | 1230 | 1255 | 1279 | 1304 | 42 | 3650 | 3668 | 3686 | 3704 |
| 18 | 1329 | 1354 | 1379 | 1405 | 43 | 3722 | 3739 | 3755 | 3772 |
| 19 | 1430 | 1455 | 1481 | 1506 | 44 | 3788 | 3804 | 3820 | 3835 |
| 20 | 1531 | 1557 | 1583 | 1608 | 45 | 3849 | 3864 | 3878 | 3891 |
| 21 | 1634 | 1660 | 1685 | 1711 | 46 | 3905 | 3917 | 3929 | 3941 |
| 22 | 1737 | 1763 | 1789 | 1814 | 47 | 3952 | 3963 | 3973 | 3982 |
| 23 | 1840 | 1866 | 1892 | 1918 | 48 | 3990 | 3998 | 4005 | 4011 |
| 24 | 1944 | 1970 | 1996 | 2022 | 49 | 4015 | 4018 | | |

* THEORETICAL CALIBRATION IS NOT INTENDED FOR LEGAL MEASUREMENT OF PRODUCT VOLUMES!